



SRR25ZS-W

2.5kW

Specifications

Nominal cooling capacity		kW	2.5
Nominal heating capacity		kW	3.4
Sound power level	Cooling	dB(A)	56
	Heating	dB(A)	59
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)	37 / 33 / 30 / 24
	Heating(Hi/Me/Lo/Ulo)	dB(A)	40 / 37 / 34 / 28
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min	9.5 / 8.5 / 6.5 / 4.5
	Heating(Hi/Me/Lo/Ulo)	m ³ /min	10.0 / 9.0 / 8.0 / 6.0
Available external static pressure		Pa	35(Initial static pressure with air filter : 5Pa)
Exterior dimensions (H×W×D)		mm	200×750×500
Net weight		kg	20.5
Refrigerant piping size	Liquid / Gas	mm (ø inch)	6.35(1/4") / 9.52(3/8")
Bottom air inlet kit (option)			UT-BAT1EF

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics

Unit: mm

Models SRR25ZS-W, 35ZS-W

Space for installation and service

